

Farmer's Friend

**Bimercol**  
By Diskubota

**LANCER**  
EMPOWERING FARMERS



## KENCHUA KH SERIES

Model : 130-180-185-200-225-230-260-290  
Require HP : 65 to 250  
Require KW : 48 to 186

### Features / Características / Caractéristiques




Clod -Breaking Blade




Wearing Point



Easy Shank Width  
Adjustment




Shear Bolt Safety  
Mechanism




Optional Roller



Wear resistant shank  
protection



Rear Roller Height  
Adjustment



Side Guard Plates



Lancer Kenchua KH Series Sub-soiler has range of 130 CM to 290CM, Which can be coupled with 65 to 250 HP tractors. It is mainly Made from Virgin Material with rigid structure, High Strength material in Shank and Point with perfect finish to reduce load on tractor.

#### Standard Equipment

- Shank thickness 30 mm
- Shank width adjustable
- Reversible quick-release blade
- Shear Bolt Safety Mechanism
- Advanced Tool Kit.

#### On Request

- Wear resistant shank protection
- Clod-breaking blades
- Mechanical roller
- Wear point blade



El subsolador Lancer Kenchua KH Series tiene un rango de 130 CM a 290 CM, que se puede acoplar con tractores de 65 a 250 HP. Está hecho principalmente de material virgen con estructura rígida, material de alta resistencia en vástago y punta con acabado perfecto para reducir la carga en el tractor.

#### Equipamiento estándar

- Espesor del vástago 30 mm
- Ancho de mango ajustable
- Cuchilla reversible de liberación rápida
- Mecanismo seguridad de perno de seguridad
- Kit de herramientas avanzado.

#### Bajo pedido

- Protección de vástago resistente al desgaste
- Cuchillas para romper terrones
- Rodillo mecánico
- Hoja de punta de desgaste



La sous-soleuse Lancer Kenchua KH Series est d'une gamme de 130 CM à 290 CM, qui peut être couplée à des tracteurs de 65 à 250 HP. Il est principalement fabriqué à partir de matériaux vierges avec une structure rigide, un matériau à haute résistance en tige et en pointe avec une finition parfaite pour réduire la charge sur le tracteur.

#### Équipement standard

- Épaisseur de tige 30mm
- Largeur de tige réglable
- Lame réversible à dégagement rapide
- Mécanisme de sécurité pour boulon de cisaillement
- Kit d'outils avancés.

#### Sur demande

- Protection de tige résistante à l'usure
- Lames brise-mottes
- Rouleau mécanique
- Lame à point d'usure

### Technical Details / Detalles técnicos / Détails techniques

| Model No.                          |  | Unit | KH 130   | KH 180   | KH 185   | KH 200    | KH 225    | KH 230    | KH 260    | KH 290    |
|------------------------------------|--|------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|
| Working width                      |  | mm   | 1850     | 1850     | 1850     | 2000      | 2300      | 2300      | 2600      | 2900      |
| Number of shanks                   |  | No   | 4        | 4        | 5        | 5         | 5         | 7         | 7         | 7         |
| Center Distance between two shanks |  | mm   | 465-545  | 465-545  | 325-410  | 345-445   | 465-521   | 310-346   | 345-396   | 375-445   |
| Working depth                      |  | mm   | 550      | 550      | 550      | 550       | 550       | 550       | 550       | 550       |
| Overall width                      |  | mm   | 1900     | 1900     | 1900     | 2050      | 2350      | 2350      | 2650      | 2950      |
| Overall Height                     |  | mm   | 1510     | 1410     | 1510     | 1510      | 1510      | 1510      | 1510      | 1510      |
| Weight Without Roller              |  | Kg   | 800      | 795      | 850      | 885       | 930       | 1070      | 1175      | 1210      |
|                                    |  | Lbs  | 1764     | 1753     | 1874     | 1951      | 2050      | 2359      | 2590      | 2668      |
| Weight With Roller                 |  | Kg   | 1055     | 1095     | 1120     | 1165      | 1230      | 1380      | 1500      | 1560      |
|                                    |  | Lbs  | 2326     | 2414     | 2469     | 2568      | 2712      | 3042      | 3307      | 3439      |
| Tractor power                      |  | HP   | 65 - 130 | 80 - 130 | 85 - 130 | 100 - 160 | 120 - 180 | 150 - 200 | 160 - 200 | 190 - 250 |
|                                    |  | KW   | 48 - 97  | 60 - 97  | 63 - 97  | 75 - 119  | 89 - 134  | 112 - 149 | 119 - 149 | 141 - 186 |



## LANCER LASER TECH LTD.

Survey No-1434P/2, Chhatral-Mehsana Highway, Rajpur, Ta-Kadi, Dist. Mehsana, Gujarat, India. 382715.

+912764-278801/02/03/04 sales@lanceragrico.com www.lanceragrico.com +91 88 99 33 55 33



Scan and Get Main Catalogue